

friendlytiles
clever 



friendly carpet tiles
featuring GreenTag certification

ecospecifier global
GREEN TAG
CERTIFIED




GreenRate | Level A

innovation & inspiration

| *Signature*™
carpettileconcepts

for 100% GreenStar Points



witty 1203



strategic 1206




versatile 2504



talented 2508



qualified 1208



brilliant 2505



capable 1209



skill 1211

product construction
yarn/fibre
pile weight
pile height
gauge
tile size
total thickness
total weight
carton size
co-ordinates

friendly tiles, clever
textured loop pile
solution dyed nylon
560g/m²
4.5mm to 2.5mm
1/10
500mm x 500mm
6.5mm
4.6kg/m²
5sqm
all friendly carpet tiles

dimensional stability
backing
electrostatic propensity
fire rating ISO 9239.1
recommended adhesive
installation method

<0.15%
Thermo Bak,Thermo-cycle Bak, Comfi Bak (PET)**
<2.0kv
4.3 kw/m² critical radiant flux
RLA Polymers GS300
quarter turn

GreenStar certification
availability

100% GreenStar points
GreenTag GreenRate
in stock

ecospecifier global
GREEN TAG
CERTIFIED



* PC: Patient Care Areas † NSB: Non Sprinkled Buildings

*Signature*TM
floorconcepts

tel 03 9401 0888
fax 03 9401 0866
signaturefloors.com.au

****contact your sales consultant for specifications**

terms & conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms and Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification. 12/2011©