

flexorubber  
**contours** 



Flexo rubber flooring  
features GreenTag certification

ecospecifier global  
**GREEN TAG**  
CERTIFIED



GreenRate | Level A

innovation & inspiration


| *Signature*<sup>TM</sup>  
rubberconcepts

function and fashion go hand-in-hand


intellitiles  
**contours** 




**sun rise** 402




**devils marble** 510



**lady bird** 503




**forest berry** 052




**lily pad** 841




**rain drop** 923




**sea urchin** 972




**hay bale** 463




**lotus pod** 341



**ocean rock** 201



**pebble stone** 304



**black beetle** 020

**product**  
**tile size**  
**total thickness**  
**dimensional stability**  
**electrostatic propensity**  
**fire rating ISO 9239.1**  
**carton size**

flexo rubber, contours  
500mm x 500mm  
3.0mm (including 0.6mm stud height)  
<0.20%  
<2.5kv  
9.4 kw/m<sup>2</sup> critical radiant flux  
5sqm

**recommended adhesive**  
**installation method**

UZIN KE 66, KR430 see guidelines  
direct stick

**GreenStar**  
**certification**  
**availability**

100% GreenStar points  
GreenTag GreenRate  
in stock

ecospecifier global  
**GREEN TAG**  
**CERTIFIED**



**Traffic**

Extra  
Heavy Duty  
Commercial 

**Warranty**

15 Year  
Limited 

**Fire**

Suitable  
All Areas 

**Green**

100%  
GreenStar  
Points 

**Slip**

Slip  
Resistant  
R9 

*Signature*<sup>TM</sup>  
floorconcepts

tel 03 9401 0888  
fax 03 9401 0866

**signaturefloors.com.au**

**terms & conditions:** Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms and Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification. 12/2011©