

friendlytiles
earth 



friendly carpet tiles
featuring GreenTag certification

ecospecifier global
GREEN TAG
CERTIFIED




GreenRate | Level A


innovation & inspiration

| *Signature*TM
carpettileconcepts

for 100% GreenStar Points



arctic 602




alps 601




oceans 603



hemisphere 652




axis 606




equator 607



planet 608



orbit 651



continents 506



latitude 701



longitude 703



atmosphere 501

product construction
yarn/fibre dye method
pile weight
pile height
gauge
tile size
total thickness
total weight
carton size

friendly tiles, earth
tufted high & low loop
Antron Lumena®
solution dyed
580g/m²
4.0mm to 2.5mm
1/10
500mm x 500mm
6.5mm
4.7kg/m²
5sqm

dimensional stability
backing
electrostatic propensity
fire rating ISO 9239 1
recommended adhesive
installation method

<0.10%
Thermo Bak, Thermo-cycle Bak, Comfi Bak (PET)**
<2.0kv
7.4 kw/m² critical radiant flux
RLA Polymers GS300
quarter turn

GreenStar certification
availability

100% GreenStar points
GreenTag GreenRate
in stock

ecospecifier global
GREEN TAG
CERTIFIED



Signature™
floorconcepts

tel 03 9401 0888
fax 03 9401 0866
signaturefloors.com.au

****contact your sales consultant for specifications**

terms & conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms and Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification. 12/2011©