

friendlytiles
tundra 



friendly carpet tiles
featuring GreenTag certification

ecospecifier global
GREEN TAG
CERTIFIED




GreenRate | Level A


innovation & inspiration

| *Signature*™
carpettileconcepts


for 100% GreenStar Points




cloudberry 3062



dwarf birch 3046



moss 3052



purple saxifrage 3084




lake 3061




storm cloud 2088



arctic dust 2075



permafrost 2049




musk ox 3094




midnight 2074




vole 2027




lemming 3013




husky 2033



caribou 2073



lichen 2093



elk 2065

product construction yarn/fibre dye method pile weight pile height gauge tile size total thickness total weight carton size

friendly tiles, tundra level loop Antron Lumena® solution dyed 580g/m² 4.0mm 1/10 500mm x 500mm 6.5mm 4.7kg/m² 5sqm

dimensional stability backing electrostatic propensity fire rating ISO 9239 1 recommended adhesive installation method

<0.10% Thermo Bak, Thermo-cycle Bak, Comfi Bak (PET)** <2.0kv 8.6 kw/m² critical radiant flux RLA Polymers GS300 quarter turn, directional

GreenStar certification availability

100% GreenStar points GreenTag GreenRate in stock

ecospecifier global
GREEN TAG CERTIFIED



*Signature*TM
floorconcepts

tel 03 9401 0888
fax 03 9401 0866
signaturefloors.com.au

****contact your sales consultant for specifications**

terms & conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms and Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification. 12/2011©