

ROYA tiles™



waves

Signature
floorcoverings®
Quality. Style. Inspiration.



green building council australia
MEMBER

ROYA tiles™ | waves

TECHNICAL SPECIFICATIONS

Product	Roya Tiles, Waves
Construction	Textured Loop Pile
Yarn/Fibre	100% Solution Dyed Polypropylene
Dye Method	Solution Dyed
Pile Weight	720g/m ²
Pile Height	4.3mm to 4.0mm
Gauge	1/10
Tile Size	500mm x 500mm
Backing	Thermoplastic with reinforced fibre glass
Total Thickness	7.5mm
Total weight	5.6kg/m ²
Dimensional Stability	<0.15%
Electrostatic Propensity	<2.0kv
Fire Rating ISO 9239.1	1.2 kw/m ² Critical Radiant Flux
Adhesive	ECO-800 Pressure Sensitive Low VOC
Installation Method	Quarter Turn



*Not Suitable for Patient Care Areas



Signature Floorcoverings Pty Ltd ABN 45 007 172 938
 13 Wurundjeri Drive Epping 3076 Victoria Australia
 Phone 1800 150 554 Fax +613 9401 0866 www.signaturefloors.com.au

Terms and Conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms and Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification.

Disclaimer: This brochure is presented for informational purposes only. Every effort is made to ensure that carpet images are of an accurate representation of the product. However, they are for illustrative purposes only and colour variations may occur in actual product, and between die series. Please note that lineal patterns when installed directional, may produce an undesired effect when lines of the same colour meet on two edges. Installers need to monitor this during installation and reposition tiles where appropriate. Patterns that are random in nature may contain additional colour ways to the ones displayed on the samples. Please consult your commercial sales consultant for further information.