

flexorubber
textures 



Flexo[®] rubber flooring
features GreenTag certification

ecospecifier global
GREEN TAG
CERTIFIED




GreenRate | Level A

innovation & inspiration

| *Signature*[®]
rubberconcepts



zesty lemon 009A



blistering sun 507A



delicate butterfly 505A



spikey wattle 503A



juicy berries 052A



prickly pear 591A



thorny thistle 592A



lush forest 802A



spiny fern 826A



slimy frog 841A



frosty glacier 908A



tranquil lake 861A



glistening dew 871A



flowing stream 923A



sandy beach 431A



rugged land 462A



murky creek 463A



feathery swan 020A



smooth stone 201A



bumpy trail 332A



still water 921A



misty cave 033A

product
tile size
total thickness
dimensional stability
electrostatic propensity
fire rating ISO 9239.1
carton size

flexo® rubber, textures
500mm x 500mm
3.0mm
<0.20%
<2.5kv
9.4 kw/m² critical radiant flux
5sqm

installation method
recommended adhesive

direct stick
Signature acrylic rubber or
2 part adhesive see guidelines

GreenStar
certification
availability

100% GreenStar points
GreenTag GreenRate
in stock



tel 613 9401 0888
fax 613 9401 0866
signaturefloors.com.au

terms & conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms and Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification. 10/2016©