signatureLVT secret advantage



Install CLICK Underlay

Signature Floors' Secret Advantage™ Underlay for CLICK LVT floors smooths out small irregularities* to create the ideal foundation.

CLICK Underlay can be laid over existing floor coverings like ceramic tiles, lino, rubber, PVC, laminate, parquet and level floorboards, as long as the sub floor is clean, flat, dry and dustfree. The sub floor should also be of normal porosity and free from contaminating products.


CLICK Underlay should only be used in rooms with a floor temperature of minimum 18°C with a relative humidity of less than 75 %. CLICK Underlay can also be installed with underfloor slab heating.

Make sure the packaging is not damaged prior to installing. Lay the sheets joint-to-joint with the FILM SIDE FACING UP at an angle of ca. 90° counter to the laying direction of your new floor. No need to fix one sheet to another.

Separate the PET-film from the sheet and begin laying your new Signature CLICK floor according to the fitting instructions. Do not use primer on **CLICK Underlay**. **CLICK Underlay** can be cut easily with a knife.

*irregularities no bigger than 5mm wide & 2mm deep, such as tile grout lines.









underlay prevents show-through of sub-floor irregularities <2mm deep & <5mm wide

The Secret Advantage!

Technical Data

Composition: Permanent resilient underlayment with mineral fillers & Polyurethane binder

Thickness: $1.5 \text{ mm} (\pm 0.15 \text{ mm})$

Roll format: approx. 10 m x 1 m (10m² per roll)

Weight/m2: $1.5 \text{ kg/m}^2 \text{ ($\pm 0.15 \text{ kg/m}^2$)}$

Weight per roll: 15 kg/roll

Fire Rating: Bfl- S1as per EN 13501-1

Acoustic: ΔLw= 12dB in combination with 4.5mm Click LVT AS/NZE 140-8



Warmer keeping warmth in the room



Quieter insulates from noise



Softer more comfortable underfoot



Protects sub-floor; smoothes irregularities



Fast easy to install; walk on straight away

Fast!
No glue, limited preparation & ready to walk on straight away



Signature Floorcoverings Pty Ltd
ABN 45 007 172 938
PO Box 1122 Epping VIC 3076
13 Wurundjeri Drive, Epping VIC 3076 Australia
Tel: 03 9401 0888 Fax: 03 9401 0866
signaturefloors.com.au