



innovation streamlined with
versatility in mind

innovation & inspiration

| *Signature*[®]
floorconcepts

innovation streamlined with versatility in mind



innovation streamlined with versatility in mind



product construction
 multi-level loop
 solution dyed nylon

yarn/fibre
 646g/m²

pile weight
 4mm

pile height
 1/10

gauge
 500mm x 500mm

tile size
 7.0mm (Thermo Bak™)
 9.5mm (Comfi Bak®)

total thickness
 5m²

carton size
 5.0kg/m² (Thermo Bak™)
 4.2kg/m² (Comfi Bak®)

total weight
 <0.15%

dimensional stability
 Thermo Bak™, Comfi Bak®

electrostatic propensity
 <2.0kv

fire rating ISO 9239.1
 6.5 kw/m² critical radiant flux (Thermo Bak™)
 9.0 kw/m² critical radiant flux (Comfi Bak®)

recommended adhesive
 RLA Polymers GS300

installation method
 quarter turn, directional, ashlar, brick

Comfi Bak® option
 in stock

shapes option
 in stock or 50m² minimum

availability
 in stock



Declare.





Signature[™]
floorconcepts

au 03 9401 0888
nz 0800 150 555
signaturefloors.com.au
signaturefloors.co.nz

Terms & Conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms & Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification. 06/2018©