

intellitiles
rhythm 



intelligent technology
combined with smart benefits

innovation & inspiration

| *Signature*[®]
carpettileconcepts

for total flexibility & cost efficiency



cadence 100



pulse 200



symmetry 300



beat 400



flow 500



frequency 600



tempo 700

product construction
yarn/fibre
pile weight
pile height
gauge
tile size
total thickness

carton size
total weight

dimensional stability
backing

intelli tiles, rhythm
 multi-level loop
 solution dyed nylon
 580g/m²
 3.5mm
 1/12
 500mm x 500mm
 6.5mm (Thermo Bak™)
 9.0mm (Comfi Bak®)
 5m²
 4.5kg/m² (Thermo Bak™)
 4.2kg/m² (Comfi Bak®)
 <0.15%
 Thermo Bak™, Comfi Bak®

electrostatic propensity
fire rating ISO 9239.1
recommended adhesive
installation method

co-ordinates with availability

<3.0kv
 >4.5 kw/m² critical radiant flux
 RLA Polymers
 quarter turn, ashlar, brick

all intelli and friendly tiles
 in stock

Traffic

Extra Heavy Duty Commercial

Warranty

15 Year Limited

Fire

Suitable All Areas

Stain/Soil

Ultragard



Signature[®]
 floorconcepts

au 03 9401 0888
 nz 0800 150 555
signaturefloors.com.au
signaturefloors.co.nz