

flexorubber
contours X



Flexo[®] rubber flooring
features GreenTag certification

ecospecifier global
GREEN TAG
CERTIFIED



GreenRate | Level A

innovation & inspiration

| *Signature*[®]
rubberconcepts

function and fashion go hand-in-hand



sun rise 402L




devils marble 510L



lady bird 503L




forest berry 052L



hay bale 463L



drift wood 431L



lily pad 841L




fresh air 871L




rain drop 923L




sea urchin 972L




black beetle 020L



ocean rock 201L



volcanic ash 033L



pebble stone 304L

product
tile size
total thickness
dimensional stability
electrostatic propensity
fire rating ISO 9239.1
carton size

flexo® rubber, contours
500mm x 500mm
3.0mm (including 0.6mm stud height)
<0.20%
<2.5kv
9.4 kw/m² critical radiant flux
5sqm

installation method
recommended adhesive

direct stick
Signature acrylic rubber or
2 part adhesive see guidelines

GreenStar
certification
availability

100% GreenStar points
GreenTag GreenRate
in stock

ecospecifier global
GREEN TAG
CERTIFIED



GreenRate | Level A

Traffic



Warranty



Fire



Green



Slip



IN STOCK



Signature[®]
floorconcepts

tel 613 9401 0888

fax 613 9401 0866

signaturefloors.com.au