

flexorubber structures X



Flexo[®] rubber flooring
R10 slip resistant roll rubber

ecospecifier global
GREEN TAG
CERTIFIED




GreenRate | Level A


innovation & inspiration

Signature[®]
rubberconcepts

function and fashion go hand-in-hand




honey bee 009



orange peel 510




poppy field 503



rose petal 052




blue tongue 871



rock pool 923



ink well 921




crushed velvet 533




palm tree 841




olive branch 802




mud brick 462




quail egg 431




silver fox 033



gun metal 332



cinder block 201



dark night 020

product
roll width
total thickness
dimensional stability
electrostatic propensity
fire rating ISO 9239.1
roll size

flexo® rubber, structures
1.2m
2.0mm
<0.20%
<2.5kv
>4.5 kw/m² critical radiant flux
15 l/m

installation method
recommended adhesive

direct stick
Signature acrylic rubber or
2 part adhesive see guidelines

GreenStar
certification
availability

100% GreenStar points
GreenTag GreenRate
in stock



Traffic Extra Heavy Duty Commercial 	Warranty 15 Year Limited 	Fire Suitable All Areas 	Green 100% GreenStar Points 	Slip Slip Resistant R10 	IN STOCK 
---	--	---	---	---	--



tel 613 9401 0888
fax 613 9401 0866
signaturefloors.com.au

terms & conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms and Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification. 10/2016©