

DYNAMIC



DYNAMIC CRUSH 300

au 1800 150 554
nz 0800 150 555
signaturefloors.com.au
signaturefloors.co.nz

Signature

DYNAMIC



SPECIFICATIONS

Product	Dynamic
Product Category	Carpet Plank
Construction	Multi-level Loop
Yarn/Fibre	Solution Dyed Nylon
Pile Weight	646g/m ² (19oz)
Pile Height	4mm
Gauge	1/12
Tile Size	250mm x 1000mm
Total Thickness	6.5mm
Total Weight	5.0kg/m ²
Carton Size	5m ²

CUSTOM OPTIONS

Thermo Bak[®]	In stock
Comfi Bak[®]	50m ² minimum
Flexi Bak[®]	50m ² minimum
Shapes by Signature[®]	50m ² minimum

INSTALLATION METHODS



BRICK



BASKETWEAVE



ASHLAR



HERRINGBONE

PERFORMANCE

Dimensional Stability	<0.15%
Backing	Thermo Bak [®]
Electrostatic Propensity	<3.0kv
Recommended Adhesive	RLA Polymers GS300
Rating	Commercial Extra Heavy Duty
Warranty	15 Year
Fire Rating ISO 9239.1	5.9kw/m ² Critical Radiant Flux Suitable all areas
Stain/Soil	Ultra Gard

SUSTAINABILITY

GreenTag[®] GreenRate Level A
 Declare Labels
 WELL & LBC Eligible

TECHNICAL DOCUMENTS

[Technical Information Guide](#)
[Care and Maintenance Guide](#)
[Warranty Guide](#)

Our manufacturing process ensures no two planks are the same. Please note that there may be batch variations from different dye lots.