









500PL

SPECIFICATIONS

800PL

700PL

600PL

900PL

product

high loop, low cut construction yarn/fibre solution dyed nylon 850g/m² pile weight pile height 4mm 1/10" gauge plank size 250mm x 1000mm total thickness 7.5mm carton size 5m² total weight 5.2kg/m² dimensional stability < 0.15% Thermo Bak™ backing <3.0kv electrostatic propensity fire rating ISO 9239.1 >4.5kw/m² critical radiant flux recommended adhesive RLA Polymers GS300 installation method ashlar, herringbone availability in stock 50m² min Comfi Bak® option customise Shapes™ 50m² min traffic extra heavy duty commercial warranty 15 year limited suitable all areas stain/soil Ultra Gard (thermo chemical treatment) sustainability GreenTag® Green Rate Level A EPDs and Declare labels WELL eligible

norse

400PL



300PL





100PL

Our manufacturing process ensures no two planks are the same. Please note that there may be batch variations from different dye lots. Comfi Bak® - optional backing for enhanced comfort. 50m² minimum order applies. Available in Shapes by Signature®. 50m² minimum order applies.

FRONT COVER: NORSE 067







NORSE 108, 105, 102, **MALMO** 700



au 1800 150 554 nz 0800 150 555 signaturefloors.com.au Limitations of the printing process may not represent the actual color of the product. Please refer to samples for final colour selection

Terms & conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Product may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms & Conditions of Sale. Please refer to our Technical Information Manual, Maintenance Guide & Warranty Guide for further clarification. © Signature Floors 06/2020