LAYERS



au 1800 150 554 nz 0800 150 555 signaturefloors.com.au signaturefloors.co.nz Signature



LAYERS



SPECIFICATIONS	
Product	Layers Semi Custom Modular
Construction	Multi-level Loop
Yarn/Fibre	Solution Dyed Nylon & Nylon 6.0
Pile Weight	1020g/m² (30oz)
Pile Height	5.5mm
Gauge	1/10
Tile Size	Refer to shape options in brochure
TotalThickness	8.5mmThermoBak® 10.5mmComfiBak®
Total Weight	6kg/m²ThermoBak® 5.8kg/m²ComfiBak®
Carton Size	4m ² (varies depending on shape selection)

CUSTOM OPTIONS	
Thermo Bak®	100m² minimum
Comfi Bak®	100m² minimum
Shapes by Signature®	100m² minimum
Base Design	Pure Planks – Base
Colour Option	Vivid 202

INSTALLATION METHODS - Depending on Shape Selection



















PFR		RAAR	ICE
PFR	CUR	IVIAI	WL.F

Dimensional Stability	<0.15%		
Backing	Thermo Bak $^{ ext{@}}$ Comfi Bak $^{ ext{@}}$		
Comfi Bak® is not recommended for Pentagon, Hexagon, Trapezoid, Right Angle & Triangle			
Electrostatic Propensity <3			
Recommended Adhesiv	ve RLA Polymers GS300		
Rating	Commercial Extra Heavy Duty		
Warranty	15 Year Limited		
Fire Rating ISO 9239.1	5.3kw/m ² Critical Radiant Flux (Thermo Bak®)		

6.1kw/m² Critical Radiant Flux (Comfi Bak®)

Suitable all areas

SUSTAINABILITY

GreenTag® GreenRate Level A EPDs and Declare Labels WELL & LBC Eligible

TECHNICAL DOCUMENTS

Technical Information Guide Care and Maintenance Guide Warranty Guide

Our manufacturing process ensures no two tiles are the same. Please note that there may be batch variations from different dye lots.







