# **AWTA PRODUCT TESTING**

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

### **TEST REPORT**

Client: Signature Floorcoverings Pty Ltd

13 Wurundjeri Drive Epping VIC 3076 **Test Number** : 22-003407

Issue Date : 29/09/2022 Print Date : 29/09/2022


Order Number: 118172

Sample Description Clients Ref : "Prism Planks Reflect"

Loop pile carpet plank
Colour: Multicolour
End Use: Flooring

Nominal Composition : Solution Dyed Nylon Nominal Mass per Unit Area/Density : 748g/m2

Nominal Thickness: 7mm



279279 60254 Page 1 of 3

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing Accreditation Numbers: 983, 985, and 1356

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.



MICHAEL A. JACKSON B.Sc.(Hons)

Fiona McDonald

APPROVED SIGNATORY

# AWTA PRODUCT TESTING

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

### **TEST REPORT**

Client: Signature Floorcoverings Pty Ltd

13 Wurundjeri Drive Epping VIC 3076 **Test Number** : 22-003407 **Issue Date** : 29/09/2022

Print Date : 29/09/2022

118172

AS ISO 9239.1-2003 Reaction to Fire Tests for Floorings. Determination of the Burning Behaviour using a

**Radiant Heat Source** 

Date of Sample Arrival

31-08-2022

Order Number:

**Date Tested** 

28-09-2022

CHF Value	1	2	3	Mean	
CHF value	ı	2	3	wean	
Length	5.3	-	-	-	kW/m²
Width	4.9	5.1	4.3	4.8	kW/m²
HF-30 Value	1	2	3	Mean	
Length	5.8	-	-	-	kW/m²
Width	5.3	5.3	6.3	5.6	kW/m²
Smoke Value	1	2	3	Mean	
Length	212	-	-	-	%.min
Width	196	170	151	172	%.min

279279 60254 Page 2 of 3

 Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing Accreditation Numbers: 983, 985, and 1356

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.



MICHAEL A. JACKSON B.Sc.(Hons)

Fiona McDonald

APPROVED SIGNATORY



Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

#### **TEST REPORT**

Client: Signature Floorcoverings Pty Ltd

13 Wurundjeri Drive Epping VIC 3076 **Test Number** : 22-003407 **Issue Date** : 29/09/2022

 Issue Date
 : 29/09/2022

 Print Date
 : 29/09/2022

Order Number: 118172

Observations:

Melting

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

Sample was conditioned in accordance with BSEN 13238:2010 at a temperature of 23±2°C and relative humidity of 50±5% for a minimum of 48 hours prior to testing.

Results in accordance with section 8.4 have not been included in the report. They are available upon request.

Each specimen was adhered to a substrate of 6mm thick fibre reinforced cement board using Roberts 656 adhesive and clamped prior to testing.

279279 60254 Page 3 of 3

Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing Accreditation Numbers: 983, 985, and 1356

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.



MICHAEL A. JACKSON B.Sc.(Hons)

Fiona McDonald

APPROVED SIGNATORY