

RAPID




RAPID TRIGGER 230

au 1800 150 554
nz 0800 150 555
signaturefloors.com.au
signaturefloors.co.nz

Signature


RAPID



ACTIVE
130 | 130CB




PROMPT
106 | 106CB




SPORTIVE
113 | 113CB




SWIFT
108 | 108CB




READY
105 | 105CB



TRIGGER
230 | 230CB




DEXTEROUS
206 | 206CB



WHIRLWIND
213 | 213CB



BRISK
208 | 208CB



LIGHTNING
205 | 205CB

SPECIFICATIONS

Product	Rapid
Product Category	Carpet Tile
Construction	Level Loop
Yarn/Fibre	Solution Dyed Nylon
Pile Weight	540g/m ² (16oz)
Pile Height	3.0mm
Gauge	5/64
Tile Size	500 x 500mm
Total Thickness	6.0mm ThermoBak® 8.5mm ComfiBak®
Total Weight	4.1kg/m ² ThermoBak® 4.1kg/m ² ComfiBak®
Carton Size	5m ²

CUSTOM OPTIONS

Thermo Bak®	In stock
Comfi Bak®	In stock
Flexi Bak®	50m ² minimum
Shapes by Signature®	50m ² minimum

INSTALLATION METHODS



QUARTER TURN

PERFORMANCE

Dimensional Stability	<0.15%
Backing	Thermo Bak® Comfi Bak®
Electrostatic Propensity	<3.0kv
Recommended Adhesive	RLA Polymers GS300
Rating	Commercial Extra Heavy Duty
Warranty	15 Year
Fire Rating ISO 9239.1	6.5kw/m ² Critical Radiant Flux (ThermoBak®) 7.6kw/m ² Critical Radiant Flux (Comfi Bak®) Suitable all areas
Stain/Soil	Ultra Gard

SUSTAINABILITY

GreenTag® GreenRate Level A
EPDs And Declare Labels
WELL & LBC Eligible

TECHNICAL DOCUMENTS

[Technical Information Guide](#)
[Care and Maintenance Guide](#)
[Warranty Guide](#)

Our manufacturing process ensures no two tiles are the same. Please note that there may be batch variations from different dye lots.