

STRIKE II
STRIKE II




STRIKE II NICKEL KRYPTON 2-600-045CB

au 1800 150 554
nz 0800 150 555
signaturefloors.com.au
signaturefloors.co.nz


Signature

STRIKE II


STRIKE II




NICKEL PHOSPHORUS
2-600-189CB




NICKEL SELENIUM
2-600-169CB




NICKEL KRYPTON
2-600-045CB




NICKEL HELIUM
2-600-132CB




NICKEL CHROMIUM
2-600-071CB




NICKEL XENON
2-600-103CB




GRAPHITE OXYGEN
2-300-019CB




GRAPHITE NITROGEN
2-300-021CB




GRAPHITE SULPHUR
2-300-124CB



GRAPHITE ARGON
2-300-107CB



GRAPHITE HYDROGEN
2-300-137CB



GRAPHITE IODINE
2-300-054CB

SPECIFICATIONS

Collection	Strike II
Product	Strike II
Product Category	Carpet Tile
Construction	Textured Loop & Tip Shear
Yarn/Fibre	Solution Dyed Nylon
Pile Weight	612g/m ² (18oz)
Pile Height	4mm
Gauge	1/12
Tile Size	500 x 500mm
Total Thickness	10mm
Total Weight	4.4kg/m ²
Carton Size	5m ²

CUSTOM OPTIONS

Comfi Bak[®]	In stock
Flexi Bak[®]	50m ² minimum
Thermo Bak[®]	50m ² minimum
Shapes by Signature[®]	50m ² minimum

INSTALLATION METHODS



ASHLAR



QUARTER TURN



BRICK



DIRECTIONAL



RANDOM

PERFORMANCE

Dimensional Stability	<0.15%
Backing	Comfi Bak [®]
Electrostatic Propensity	<3.0kv
Recommended Adhesive	RLA Polymers GS300
ACCS Rating	Commercial Extra Heavy Duty
Warranty	15 Year
Fire Rating ISO 9239.1	5.2kw/m ² Critical Radiant Flux Suitable all areas
Stain/Soil	Ultra Gard

SUSTAINABILITY

GreenTag[®] GreenRate Level A
EPDs And Declare Labels
WELL & LBC Eligible

TECHNICAL DOCUMENTS

[Technical Information Guide](#)
[Care and Maintenance Guide](#)
[Warranty Guide](#)

Our manufacturing process ensures no two tiles are the same. Please note that there may be batch variations from different dye lots.