

**Product: Comfi Lay 7**

**Technical Data Sheet for Foam Underlay – AXICOMFILAY7D**

**Description of Goods**

Foam commercial underlay suitable for installation using the double stick or dual bond method of Signature Axminster Carpet on concrete floors (refer to adhesive manufacture specifications for application and guidelines)

<b>ROLL DIMENSIONS</b>	<b>LENGTH</b> 15	<b>WIDE</b> 1.37	<b>M<sup>2</sup> PER ROLL</b> 20.55
<b>Weight</b>	25.7kg per roll		
<b>Thickness</b>	7.0mm +/-10%		
<b>TOP SURFACE</b>	Stitchbrown, Kraft paper		
<b>BOTTOM</b>	Non woven fabric		

<b>Tensile Strength &amp; Elongation</b>	<b>ISO 9073.3-1989</b>	<b>L</b>	<b>W</b>
i) Mean load at breaking point		201.2 N/50mm	30.7 N/50mm
ii) Mean elongation at 40 N		3.5%	N/A
<b>Tested at Standard Conditions</b>			
i) Mean elongation at break		18.0%	5%
<b>Thickness Loss on Static - Long Term Loading</b>			
Compliance to	AS4288-2003	PASS	Table 2
<b>Soft Underlays for Textile Floor Coverings - Method for the Determination of Compress Characteristics</b>			
Compliance to	AS42800-2003	PASS	Table 2
<b>Under Lay Thickness</b>			
Compliance to	AS42800-2003	PASS	Table 2
<b>Textile Floor Covering - Mass Per Unit Area</b>			
Weight per 400 cm <sup>2</sup>	1392 g/m <sup>2</sup>	+/- 2.0%	
<b>Resistance to Breaking/and Cracking</b>			
No cracks or breaks	AS42800-2003	PASS	Table 2
Length of cracks or breaks	AS42800-2003	PASS	Table 2
Location of cracks or breaks	AS42800-2003	PASS	Table 2

**NOTE**

Specification are subject to change without notice, refer to our website for the latest information or technical bulletin