

TRAIL TILES



a true palette of contemporary shades



innovation & inspiration

Signature[®]
floorconcepts

a true palette of contemporary shades

TRAILTILES



trail pebble 400




trail slate 300



trail granite 200



trail rock 100



trail bluestone 500

product
construction
yarn/fibre
pile weight
pile height
gauge
tile size
total thickness
carton size
total weight
dimensional stability
backing
electrostatic propensity
fire rating ISO 9239.1
recommended adhesive
installation method
availability
Comfi Bak® option
customise Shapes™
traffic
warranty
fire
stain/soil
sustainability

trail
 multi-level loop
 solution dyed nylon
 612 g/m² (18oz)
 3.5mm
 1/10
 500mm x 500mm
 6mm
 5m²
 4612 g/m²
 <0.15%
 Thermo Bak™
 <3.0kv
 >4.5 kw/m² critical radiant flux
 RLA Polymers GS300
 ashlar, directional, quarter turn, brick
 in stock
 50m² minimum
 50m² minimum
 extra heavy duty commercial
 15 year
 suitable all areas
 Ultra Gard
 GreenTag® GreenRate Level A certified
 EPD and Declare labels



au 03 9401 0888
 nz 0800 150 555
signaturefloors.com.au
signaturefloors.co.nz