

VERVE+




VERVE+ DRIVE AQUA 131


au 1800 150 554
nz 0800 150 555
signaturefloors.com.au
signaturefloors.co.nz

Signature


VERVE+



DRIVE MARMALADE
153 | 153CB



DRIVE RED
135 | 135CB



DRIVE PLUM
133 | 133CB




DRIVE DENIM
119 | 119CB




DRIVE AQUA
131 | 131CB



DRIVE TEAL
121 | 121CB



DRIVE GRASSY
120 | 120CB



DRIVE PISTACHIO
102 | 102CB



DRIVE GREY
198 | 198CB



VERVE DRIVE
100 | 100CB

SPECIFICATIONS

Product	Verve+
Product Category	Carpet Tile
Construction	Multi-level Loop
Yarn/Fibre	Solution Dyed Nylon & Nylon 6.0
Pile Weight	646g/m ² (19oz)
Pile Height	4.0mm
Gauge	1/12
Tile Size	500 x 500mm
Total Thickness	7.0mm Thermo Bak® 9.5mm Comfi Bak®
Total Weight	5.0kg/m ² Thermo Bak® 4.2kg/m ² Comfi Bak®
Carton Size	5m ²

CUSTOM OPTIONS

Thermo Bak®	In stock
Comfi Bak®	In stock
Flexi Bak®	50m ² minimum
Shapes by Signature®	50m ² minimum

INSTALLATION METHODS



ASHLAR



QUARTER TURN



BRICK



DIRECTIONAL



RANDOM

PERFORMANCE

Dimensional Stability	<0.15%
Backing	Thermo Bak® Comfi Bak®
Electrostatic Propensity	<3.0kv
Recommended Adhesive	RLA Polymers GS300
ACCS Rating	Commercial Extra Heavy Duty
Warranty	15 Year
Fire Rating ISO 9239.1	5.9kw/m ² Critical Radiant Flux (Thermo Bak®) 9.3kw/m ² Critical Radiant Flux (Comfi Bak®) Suitable all areas
Stain/Soil	Ultra Gard

SUSTAINABILITY

GreenTag® GreenRate Level A
EPDs And Declare Labels
WELL & LBC Eligible

TECHNICAL DOCUMENTS

[Technical Information Guide](#)
[Care and Maintenance Guide](#)
[Warranty Guide](#)

Our manufacturing process ensures no two tiles are the same.
Please note that there may be batch variations from different dye lots.