



sustainable, fashionable flooring designed for all interiors

floorconcepts





FABRIC arrange 2727



FABRIC dimension 2622



FABRIC scheme 5215



FABRIC motion 4213



FABRIC map 2741



FABRIC create 2646



FABRIC purpose 2695



FABRIC breathe 2685



PABRIC flex 2444



FABRIC pulse 1259



FABRIC resolve 1261



FABRIC formulate 2535



FABRIC rise 1258



FABRIC touch 1260



FABRIC dash 2653



FABRIC current 1255



FABRIC enrich 1257



FABRIC flow 1263



FABRIC circulate 1254



FABRIC evolve 1256



FABRIC compose 1262

fabric





product tile size total thickness carton size total weight slip rating fire rating ISO 9239.1 scratch resistance dimensional stability backing acoustic insulation

wovn™ vinyls, fabric 500mm x 500mm 5.0mm 4sqm 3.0kg/m² P1/R9 7.6 kw/m² critical radiant flux class T contains fibre glass layer felt 19dB

underfloor heating recommended adhesive installation method co-ordinates with traffic warranty fire environmental sustainability availability

suitable PS with V1 trowel ashlar, brick, quarter turn all wovn vinyl tiles & Themo Bak™ carpet tiles class 33 heavy duty commercial 15 year commercial suitable all areas sustainable manufacturing 10% recycled content in stock

Traffic





















cover image: fabric arrange 2727 above: fabric breathe 2685



au 03 9401 0888 nz 0800 150 555

signaturefloors.com.au signaturefloors.co.nz