





ignature floors ®





Caldwell Oak ABODERG48719



Waverley Oak ABODERG4876



Tongrass Oak **ABODERG4873**



Tarkine Oak ABODERG4874



Bunyip Blackbutt ABODERG7552



Gillii Gum ABODERG7552



Wandella Oak ABODERG48712



Kinglake Oak ABODERG4871

TECHNICAL SPECIFICATIONS

Plank Size 228 x 1520mm

Total Thickness 6mm 0.50mm Wear Layer Wear Layer Treatment PU (Polyurethane)

Surface Natural embossed, true to life oak boards

Edge Design Micro V groove 4 sided

Fire Rating ISO 9239.1 Pass Slip Rating

Underfloor Heating Suitable for water based systems

Planks per Box 6 pcs/box (2.079m²)

Locking System

25 Yr Residential, 10 Yr Commercial Warranty





certified to comply with strict indoor quality emission requirements.





















- · installs directly over irregularities and existing floors
- · can be laid over ceramic and porcelain tiles
- · can be laid over concrete
- can be laid over chipboard and tongue & groove flooring
- existing floors need to adhere to the sub-floor
- · existing floor cannot be cushioned
- uneven floors require sub-floor preparation when there is a height variation more than 3mm over 1m
- · sub-floors should be clean and dry

Please refer to installation guidelines; if uncertain seek clarification prior.



au 03 9401 0888 **nz** 0800 150 555 signaturefloors.com.au signaturefloors.co.nz

Terms & Conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms & Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification.