





ignature floors R





Boden Oak

ABODERG542



Malmo Oak **ABODERG544** 



Floro Oak **ABODERG545** 



Lulea Oak

ABODERG543



Tromso Oak

ABODERG539



Vardo Oak

ABODERG540

## **TECHNICAL SPECIFICATIONS**

Plank Size 228 x 1830mm
Total Thickness 6.50mm
Wear Layer 0.50mm

Wear Layer Treatment Multi-layer quartz enhanced PUR coating Surface Natural embossed, true to life oak boards

Edge Design Micro V groove 4 sided

Fire Rating ISO 9239.1 12.1 kW/m² critical radiant flux

Slip Rating

Underfloor Heating Suitable for water based systems

Planks per Box 6 pcs/box (2.503m²)

Locking System 5

Warranty Lifetime Residential, 15 Yr Commercial





Abode has been tested and certified to comply with strict indoor quality emission requirements.





















- installs directly over irregularities and existing floors
- can be laid over ceramic and porcelain tiles
- can be laid over concrete
- can be laid over chipboard and tongue & groove flooring
- existing floors need to adhere to the sub-floor
- existing floor cannot be cushioned
- $\bullet$  uneven floors require sub-floor preparation when there is a height variation more than 3mm over 1m  $\,$
- sub-floors should be clean and dry

Please refer to installation guidelines; if uncertain seek clarification prior.



au 03 9401 0888 nz 0800 150 555 signaturefloors.com.au signaturefloors.co.nz

Terms & Conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms & Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification.