

Distinct

HYBRID FLOORING



Signature

Technical specifications

Plank size	228 x 1220mm
Total thickness	6mm
Wear layer	0.50mm
Wear layer treatment	Quartz enhanced PUR coating
Backing	Liteback
Pack size	10 pcs/box (2.78m ²)
Subfloor heating	Suitable for water based systems
Slip resistance	P4
Fire rating ISO 9239.1	Suitable all areas
Locking system	5G



waterproof surface *



scratch resistant



easy clean



stain resistant



anti bacterial



hardwearing



fire resistant



wet mop



Terms & Conditions: Due to variances in printed materials, product images shown may differ slightly from the actual product. For a true reflection of the product, we recommend visiting one of our friendly stockists. Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. *The term waterproof supports localised topical spills and short-term moisture exposure from household accidents. It does not support flooding or long-term exposure to excess sub-floor moisture. Before installing hybrid flooring in a bathroom, kitchen or laundry, please refer to the relevant building code requirements. In Australia please refer to National Construction Code Part 3.8.1 and AS3740 Waterproofing of Wet Areas within Residential Buildings. In New Zealand, please refer to Acceptable Solution E3/AS1 on our website. All product purchases are subject to Signature Floorcoverings Standard Terms & Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification.

This warranty is in addition to and does not affect your statutory rights. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law/NZ Consumer Guarantees Act 1993. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.