

Signature floors Mosman

HYBRID FLOORING



ARCHER

6 0





Technical specifications

Plank size 228 x 1520mm **Total thickness** 7.00mm (5.50mm board & 1.50mm backing) Wear layer 0.50mm Wear layer treatment Quartz enhanced PUR coating Surface Crystal emboss matte finish Backing Embossed EVA P4 Slip resistance Edge design Micro V groove 4 sided Fire rating ISO 9239.1 12.2kW/m² **Underfloor heating** Suitable for water based systems Planks per box 6 pcs/box (2.079m²) Installation method 5G Click 25 Year Residential, 15 Year Commercial Warranty

MOSMANHYB030

MOSMANHYB070



Archer MOSMANHYB010



Rickard MOSMANHYB050



Oswald MOSMANHYB090







under floor heating scratch resistant



signaturefloors





Pindari









Milton

Warringah

MOSMANHYB080

VFARS

MOSMANHYB040





Terms & Conditions: Due to variances in printed materials, product images shown may differ slightly from the actual product. For a true reflection of the product, we recommend visiting one of our friendly stockists. Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms & Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification.

This warranty is in addition to and does not affect your statutory rights. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.



Carrington MOSMANHYB020



MOSMANHYB060



MOSMANHYB100



heavy duty

fire resistant