



loft by Signature





Zinc 40862 ■■



Zura 46950 ■■



Sterling 46968 ■■



Axel 46972 ■■



Technical Specifications

	STICK	TAC
Total Thickness	2.50mm	4.50mm
Wear Layer	0.55mm	0.55mm
Wear Layer Treatment	Superguard™	Superguard™
Total Weight	4.059 g/m ²	7.575 g/m ²
Tile Size	329mm x 659mm	329mm x 659mm
Tiles per Box	16 pcs/box (3.47m ²)	7 pcs/box (1.52m ²)
Fire Rating	Bfl-s1	Bfl-s1
Slip Resistance	R10	R10
Warranty	20 Yr Residential 10 Yr Commercial	20 Yr Residential 10 Yr Commercial
Installation Method	Stick (use rec. adhesive)	Tac (use rec. adhesive)
Post Recycled Content	35%	35%



STICK

** floor prep may be required*



TAC

** floor prep may be required*



Signature
signaturefloors®

tel 613 9401 0888
fax 613 9401 0866
signaturefloors.com.au

Terms & Conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms & Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification. As per Competition & Consumer Act (CCA): "Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure." Please refer to our warranties on: www.signaturefloors.com.au 10/2017 ©